






Specification sheet




PVE 900 TIER 2

Hydraulic Power Pack

English

**Specifications :****PVE 900 TIER 2**

Diesel Engine	Volvo TAD 1643 VE-B	
Max. theoretical power	565/768	kW/HP
Max. frequency	1900	rpm
Max. operating pressure	350	bar
Hydraulic pump	Parker	
Max. oil flow	972	L/min
Diesel oil	1045	L
DEF (AdBlue) capacity	N.A.	L
Hydraulic oil	2200	L
Weight without fuel	9120	kg
Weight filled up	10000	kg



Technische Daten :

PVE 900 TIER 2




Dieselmotor	Volvo TAD 1643 VE-B	
Max. theoretische Leistung	565/768	kW/HP
Max. Drehzahl	1900	rpm
Max. Betriebsdruck	350	bar
Hydraulische Pumpe	Parker	
Max. Fördermenge	972	L/min
Diesel Öl	1045	L
DAF (AdBlue) kapazität	N.A.	L
Hydraulische Öl	2200	L
Gewicht ohne Diesel Öl	9120	kg
Gewicht	10000	kg



Spécifications

PVE 900 TIER 2

Groupe hydraulique



Spécifications

PVE 900 TIER 2

Moteur Diesel	Volvo TAD 1643 VE-B	
Puissance théorique max.	565/768	kW/HP
Max. fréquence	1900	rpm
Pression de travail max.	350	bar
Pompe hydraulique	Parker	
Débit d'huile max.	972	L/min
Huile diesel	1045	L
Capacité FED (AdBlue)	N.A.	L
Huile hydraulique	2200	L
Poids sans huile diesel	9120	kg
Poids	10000	kg






Specificaties

PVE 900 TIER 2

Hydraulisch aggregaat

Nederlands



Specificaties

PVE 900 TIER 2

Dieselmotor	Volvo TAD 1643 VE-B	
Max. theoretisch vermogen	565/768	kW/HP
Max. toerental	1900	rpm
Max. werkdruk	350	bar
Hydraulische pomp	Parker	
Max. olie doorstroming	972	L/min
Diesel olie	1045	L
DEF (AdBlue) capaciteit	N.A.	L
Hydraulische olie	2200	L
Gewicht zonder diesel	9120	kg
Gewicht	10000	kg






Especificaciones

PVE 900 TIER 2

Unidad de potencia

Español



Especificaciones

PVE 900 TIER 2

Motor de diesel	Volvo TAD 1643 VE-B	
Potencia Máxima teórica	565/768	kW/HP
Frecuencia máxima	1900	rpm
Presión máxima de trabajo	350	bar
Bomba hidráulica	Parker	
Flujo de aceite máximo	972	L/min
Gasóleo	1045	L
Capacidad DEF (AdBlue)	N.A.	L
El aceite hidráulico	2200	L
Peso sin gasóleo	9120	kg
Peso	10000	kg






Specifications

PVE 900 TIER 2

Hydraulic Power Pack

USA

Dimensions in inches



Specifications

PVE 900 TIER 2

Diesel Engine	Volvo TAD 1643 VE-B	
Max. theoretical power	565/768	kW/HP
Max. frequency	1,900	rpm
Max. operating pressure	5,076	psi
Hydraulic pump	Parker	
Max. oil flow	257	gal/min
Diesel Fuel	276	gal
DEF (AdBlue) capacity	N.A.	gal
Hydraulic oil	581	gal
Weight without fuel	20,106	lbs
Weight with fuel	22,046	lbs






Specificatii

PVE 900 TIER 2

unitate de putere hidraulica

românesc

**Specificatii :****PVE 900 TIER 2**

Motor diesel	Volvo TAD 1643 VE-B	
Puterea maxima teoretica	565/768	kW/HP
Frecventa maxima	1900	rpm
Presiune maxima de lucru	350	bar
Pompa hidraulica	Parker	
Debit maxim de ulei	972	L/min
motorină	1045	L
Capacitate rezervor aditiv AdBlue	N.A.	L
Ulei hidraulic	2200	L
Greutatea fara combustibil	9120	kg
Greutatea cu combustibil	10000	kg